



BENALU
Rue Fresnel
B.P. 10002
62801Lievain Cedex
France

Your contact : James Cleary

Telephone : 087 0523432

Email : james@tranway.ie

Date : 2026

Our reference :

TRANSWAY TRAILERS LTD
T/A FLEET SOLUTIONS LTD

UNIT 4 – BESSER DRIVE DUBLIN - 22
IRELAND

Dear customer,

Thank you very much for your interest in our company and semi-trailers.
Further to our conversation, you will find enclosed the commercial proposal with technical specifications of the semi-trailer as follows:

Semi-trailer : BULKLINER S 10600 VI H2100 - 54.7m3 - F6/C4 POS - SAF FIX (04/2026)



(Picture for illustration purposes only)

Vehicle Specification

04/2026

BULKLINER S 10600 VI H2100 - 54.7m³ - F6/C4 POS - SAF FIX

* The dash (-) means : equipment not chosen or not available on this material

Frame	95 mm step frame aluminum chassis (body with front tunnel) - 3 axles single mounting
Coupling height in loaded condition (mm)	1170
Coupling plate and king pin	Bolted steel coupling plate - Thickness 8 mm
Hanger brackets	Steel hanger brackets bolted on the aluminum frame
Insulation between steel hanger brackets and aluminum	Yes
Axles	SAF axles - Disc brakes - Diameter 430 mm - Air suspension
Wheel offset (mm)	120
Type axles	Fixed axles
Steering axle blocking	-
Distance between axles	EG distance between axles
Hubodometer	-
Tire inflating system	-
Braking system	EBS 2 sensors (2S2M) with ISO 7638 plug - Integrated stability control system
Brand anti-blocking EBS	Wabco
EBS control (Infocentre / Smartboard)	No
Front lift axle	No
Lift axle control	-
Forced lowering of front lik axle	No
Rear lift axle	Automatic control
Tires	6 x 385 / 65 R 22.5 Hankook Regional
Energy efficiency rating (Class)	A
Wet grip rating (Class)	B
External noise (dB)	69
Rims	Alcoa Durabright
BENALU chrome-plated wheel nut caps	No
Spare wheel	No
TPMS	TPMS tire pressure and temperature monitoring system (excluding spare wheel) compliant with R141 regulations
Spare wheel carrier	Without spare wheel carrier
Mud wings and mud flaps	EC individual mud wings - Anti-spray mud flaps at rear
Front landing legs	telescopic front landing legs with compensating feet
Rear bumper	Manually operated EC rear bumper
Side guards	EC folding up aluminum side guards
Type of air suspension	Air suspension with levelling valve - Conventional control
Labour / brakes	Aluminum air tank (120 liters)
Brake pressure tap	-
Lower and raise valve	Lower and raise valve (road position automatically operated)
Automatic deflating by tipping	Automatic suspension deflating valve by tipping - Quick release valve by tipping
Load pressure gauge	-
Electricity	24V electrical circuit, water proof
Braking and electrical wire case	Electrical wires & pneumatic hoses protection case
Connection support	Support at front (to the left) regrouping pneumatic and electrical connections
Electric supply system	24S24N electrical plugs (2x7 pin) + 15 pin plug on support
Lights support plate	Rear lights fitted on independent support sheets
Lighting	Rectangular rear lights with LED - Rear clearance lights "horn" type
Reverse warning horn	-
Registration plate light	Rear number plate LED light
Side marking lights	LED side marking lights - Front position lights
Working light at rear	LED white working rear light (connected to the reverse light + switch)
Working lights / Quantity	2
Ram	Non chromed eye fitted front ram – Stroke 7500 mm - Audible tipping alarm
Ram brand	Edbro
Tipping angle (°)	43
Hydraulic coupling	3/4" threaded hydraulic coupling
Pressure release valve	-
On board washing station	-
Wheel chock / Quantity	-
Towing ring	-
Tool box / Quantity	1 tool box
Fire extinguisher / Quantity	-
Full width mud flap	Full width mud flap
Body	Smooth sided aluminum body – Longitudinal side panels double wall – Reinforced version – Vertical gradient internal thickness (4 mm intermediate part) – Inner length 10.60m – Inner useful height 2100 mm – Sloped upper rails towards the inside
Floor	Body with tunnel - Floor sheet thickness 6mm

Inner useful width (mm)	2410
Floor reinforcement with longitudinal cross members	-
Doubling of upper rail profiles	-
Front wall	14° sloped front wall - Thickness 4mm - Conical dog house - 450mm reduced depth
Door	Straight oscillating tail gate - 2 clamping eye bolts in the lower part - Side locking with latches - Rubber seal on the fixed frame
Type of door panel	Ribbed door panels
Inside of the door continuous welding	No
Half locking bar	-
Door locking device	Locking of the rear oscillating door frame with 4 hooks shaft - Automatic opening pneumatically operated
Door upper hinge	Upper aluminum casted double hinges, removable and integrated in the side wall height of the body
Grain hatch	Central (aluminum)
Doors and grain hatch locking	-
Funnel on grain hatch	Grain sock with housings on grain hatch(es) and on chassis
Funnel / Quantity	1
Grain sock	-
Side door holder	-
Door side opening system	-
Rear link body/chassis	Stell tipping axis
Hyfix	HYFIX body blocking device on the chassis
Rear step ladder	-
Shovel holder / Quantity	1 Shovel holder (outside)
Ladder steps inside the body / Position	Located on the left hand-side between the front wall and the dog house
Cover sheet system	-
Cover sheet system control	-
Cover sheet system with front and rear protrusion	No
10m covering strap	No
Cover sheet color	-
Cover sheet protection mat	-
Bow supports and body bracing	Welded roof bow supports on sloped upper rails - Spacing straps
Walkway on the front wall	Aluminum walkway on the front wall - Bolted components
Walkway access	Access ladder on the left with safety chain
Ladder under the body	3.5m aluminum ladder fitted under the body
Plates and stickers	Manufacturer and vehicle id. plates
Hazardous product plates / Quantity	-
Water tank (50 L)	No
Complete painting	2 Color polyurethane paint (1 color on the body - 1 color on the chassis) acc. to RAL color range
Warranty on painting	Standard Warranty (1 year)
Chassis color	RAL 7024
Body color	RAL 9003
Color of retro-reflecting stripping on the side	White
Color of retro-reflecting stripping at rear	Red
Large "Benalu.com" logos on the side walls	No

ADDITIONAL SPECIFICATIONS :

Ref. BU26IE00002-00/01	13.5 / 24t bolted chassis frame. In accordance with specification / 01 bumper R58.03. 10mm coupling plate made with steel across the entire width of the chassis including the sliding plate
Ref. BU26IE00002-00/02	Installation and supply of PM On Board PM1155CN-BUS On-board weighing system and specific cylinder and articulation axis bearings
Ref. BU26IE00002-00/03	Additional locks to be UK style manual screw type locks. Attention make sure the arms of the steering wheels are parallel to the body
Ref. BU26IE00002-00/04	REMOVABLE. (Small ladder 1.5m with hooks). See 240001406. Rear access ladder
Ref. BU26IE00002-00/05	Rack and pinion grain hatch
Ref. BU26IE00002-00/06	Pneumatic coupling hand type C

Please find as follows our sales terms about the above mentioned semi-trailer :

Semi-trailer : BULKLINER S 10600 VI H2100 - 54.7m3 - F6/C4 POS - SAF FIX (04/2026)

Number of vehicles	: 1
Unitary sell price excluding VAT	: 67,900.00 €
Unitary amount of VAT	: 0.00 €
Unitary selling price PTI	: 67,900.00 €
Terms of payment	: Au comptant
Place of delivery	: Dublin Ireland
Delivery time requested	: 12 Weeks after confirmation of order
Tare weight ±3%	: 6,073 kg
Validity of offer	: 2 Days

Best regards

BENALU 