



BENALU France

TRANSWAY/ IRELAND

Dear customer,

Thank you very much for your interest in our company and semi-trailers.

You will find below the commercial proposal with technical specifications of the semi-trailer as follows :

2024 Semi-trailer : BULKLINER FL 10600 VI H2530 - 66m<sup>3</sup> / 86yd<sup>3</sup> - F8/C6 POS - SAF FIX (09/2022)



## Vehicle Specification

09/2022

### BULKLINER FL 10600 VI H2530 - 66m3 / 86yd3 - F8/C6 POS - SAF FIX

\* The dash (-) means : equipment not chosen or not available on this material

Frame	95 mm step frame aluminum chassis (body with front tunnel) - 3 axles single mounting
Coupling height in loaded condition (mm)	1170
Coupling plate and king pin	Bolted steel coupling plate - Thickness 8 mm
Hanger brackets	Steel hanger brackets bolted on the aluminium frame
Insulation between steel hanger brackets and aluminum	Yes
Axles	SAF axles - Disc brakes - Diameter 430 mm - Air suspension
Wheel offset (mm)	120
Type axles	Fixed axles
Steering axle blocking	-
Distance between axles	EG distance between axles
Hubodometer	-
Tire inflating system	-
Braking system	EBS 2 sensors (2S2M) with ISO 7638 plug - Integrated stability control system
Brand anti-blocking EBS	Wabco
EBS control (Infocentre / Smartboard)	No
Front lift axle	No
Lift axle control	-
Forced lowering of front lift axle	No
Rear lift axle	Without
Tires	6 x 385 / 65 R 22.5 Good Year Regional
Energy efficiency rating (Class)	B
Wet grip rating (Class)	C
External noise (dB)	71
Rims	Alcoa Durabright
BENALU chrome-plated wheel nut caps	No
Spare wheel	No
TPMS	TPMS tire pressure and temperature monitoring system (excluding spare wheel) compliant with R141 regulations
Spare wheel carrier	Without spare wheel carrier
Mud wings and mud flaps	EC individual mud wings - Anti-spray mud flaps at rear
Front landing legs	telescopic front landing legs with compensating feet
Rear bumper	Manually operated EC rear bumper
Side guards	EC folding up aluminium side guards
Type of air suspension	Air suspension with levelling valve - Conventional control
Labour / brakes	Aluminium air tank (120 litres)
Brake pressure tap	-
Lower and raise valve	Lower and raise valve (road position automatically operated)
Automatic deflating by tipping	Automatic suspension deflating valve by tipping - Quick release valve by tipping
Load pressure gauge	-
Electricity	24V electrical circuit, water proof
Braking and electrical wire case	Electrical wires & pneumatic hoses protection case
Connection support	Support at front (to the left) regrouping pneumatic and electrical connexions
Electric supply system	24S24N electrical plugs (2x7 pin) + 15 pin plug on support
Lights support plate	Rear lights fitted on independent support sheets
Lighting	Rectangular rear lights with LED - Rear clearance lights "horn" type
Reverse warning horn	Audible reverse alarm
Registration plate light	Rear number plate LED light
Side marking lights	LED side marking lights - Front position lights
Working light at rear	LED white working rear light (connected to the reverse light + switch)
Working lights / Quantity	2
Ram	Non chromed eye fitted front ram – Stroke 7500 mm - Audible tipping alarm
Ram brand	Edbro
Tipping angle (°)	43
Hydraulic coupling	3/4" threaded hydraulic coupling
Pressure release valve	-
On board washing station	-
Wheel chock / Quantity	-
Towing ring	-
Tool box / Quantity	1 tool box
Fire extinguisher / Quantity	1 piece 6 kg powder fire extinguisher in PVC box

Full width mud flap	-
Body	Smooth sided aluminium body – Extrusions inner thickness 6mm – Radiused lower rail profile (non pallet wide) – Inner length 10,60m – Inner useful height 2530mm – Sloped upper rails towards the insideSmooth sided aluminium body
Floor	Body with tunnel - Floor sheet thickness 8mm
Inner useful width (mm)	2410
Floor reinforcement with longitudinal cross members	-
Continuous welding on extrusions	-
Doubling of upper rail profiles	-
Front wall	14° sloped front wall - Thickness 4mm - Conical dog house - 450mm reduced depth
Door	Straight oscillating tail gate - 2 clamping eye bolts in the lower part - Side locking with latches - Rubber seal on the fixed frame
Type of door panel	Ribbed door panels
Inside of the door continuous welding	No
Half locking bar	-
Door locking device	Locking of the rear oscillating door frame with 4 hooks shaft - Automatic opening pneumatically operated
Door upper hinge	Upper aluminium casted double hinges, removable and integrated in the side wall height of the body
Grain hatch	Central (aluminium)
Doors and grain hatch locking	-
Funnel on grain hatch	-
Funnel / Quantity	0
Grain sock	-
Side door holder	-
Door side opening system	-
Rear link body/chassis	Stell tipping axis
Hyfix	HYFIX body blocking device on the chassis
Rear step ladder	-
Shovel holder / Quantity	1 Shovel holder (outside)
Ladder steps inside the body / Position	Front left corner
Cover sheet system	Side rolling cover sheet system - Sheet with white translucent strip - Side tension with straps - Round aluminium roof bows (camber 100mm) - Articulated, adjustable, removable and folding aside - MULTIFUNCTION cover sheet holders (straight, curved, folding aside) - Forged aluminium, cover sheet rod
Cover sheet system control	Manual control
Cover sheet system with front and rear protrusion	No
10m covering strap	No
Cover sheet colour	White (B1060 / B2060) - PVC 900 gr/m <sup>2</sup>
Cover sheet protection mat	-
Bow supports and body bracing	Welded roof bow supports on sloped upper rails - Spacing straps
Walkway on the front wall	Aluminium walkway on the front wall - Bolted components
Walkway access	Access ladder on the left with safety chain
Ladder under the body	3.5m aluminium ladder fitted under the body
Plates and stickers	Manufacturer and vehicle id. plates
Hazardous product plates / Quantity	-
Water tank (50 L)	No
Complete painting	2 Colour polyurethane paint (1 colour on the body - 1 colour on the chassis) acc. to RAL colour range
Warranty on painting	Standard Warranty (1 year)
Chassis colour	RAL 7024
Body colour	RAL 9010
Colour of retro-reflecting stripping on the side	White
Colour of retro-reflecting stripping at rear	Red
Large "Benalu.com" logos on the side walls	No

**ADDITIONAL SPECIFICATIONS :**

<i>Ref. BU24IE00010-00/01</i>	<b>13,5 / 24 t bolted chassis and 10 mm reinforced 5<sup>th</sup> wheel plate on full width of chassis</b>
<i>Ref. BU24IE00010-00/02</i>	<b>on board weighing system PM On Board PM1155CN-BUS et with sensors on ram support and rear tipping bearing</b>
<i>Ref. BU24IE00010-00/03</i>	<b>3 pairs of lashing rings</b>
<i>Ref. BU24IE00010-00/04</i>	<b>- 1 intermediate wall with air operated lock/unlock system operated by air switch inside wheel base - Stainless steel screws, seam welding - drawing D068041-20-A</b>
<i>Ref. BU24IE00010-00/05</i>	<b>bulkliner 10600 F8 FL6, "IE", inside height 2530</b>
<i>Ref. BU24IE00010-00/06</i>	<b>Rear door smooth panels with central grain hatch</b>

Please find as follows our sales terms about the above mentioned semi-trailer :

Semi-trailer : BULKLINER FL 10600 VI H2530 - 66m3 - F8/C6 POS - SAF FIX (09/2022)

**Number of vehicles** : 1

**Unitary sell price excluding VAT** : 53,000€

**Unitary amount of VAT** : 0.00€

**Unitary selling price PTI** : 53,000€

**Terms of payment** :

**Place of delivery** : Dublin

**Delivery time requested** :

**Tare weight ±3%** : 7,162 kg

**Validity of offer** : 2 Days

Best regards

 **BENALU**